

Product Datasheet	
<div>  <div>HBL23005GB -- Hubbellock Plug</div> </div>	
	 <div>2P3W, 20A 125V Max, Nylon Housing, Thermoset Interior</div>
Product Specifications	
Product Type	
Product Item	Plug
Wiring Scheme	2-Pole, 3-Wire Grounding
Multi-Rating	20A 125V, 10A 250V DC, 480V AC
Device Color	Black/White
Cord Dia.	.30"-.65" (7.6-16.5)
Blade Holder Material	Black Thermoset
Housing Material	Black nylon
Cord Clamp Material	Natural (white) nylon
Blade Material	Brass
Terminal Clamp Material	.020" (.5) Brass
Terminal Screw Material	Brass
Ground Screw Material	Brass (Green)
Cord Clamp Screw Material	Steel-zinc-plated
Body Holding Screw Material	Steel-zinc-plated
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	15A #14AWG; 20A #12AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP30
UPC Number	783585017389
Weight in LBs	0.27